

9390 BATTERY POWERED INDICATOR

FEATURES & BENEFITS

- Large 1 in (25.4 mm) high contrast LCD display
- 6 digits
- 100,000 graduations
- Powers up to 4 load cells
- Battery-powered
- 15 updates/second typical
- Configurable standby mode for extended battery life
- Full front-panel digital calibration & configuration
- Three-stage digital filtering
- Full duplex RS-232

SPECIFICATIONS

ELECTRICAL		
Excitation Voltage – VDC		5 ±0.5, 4 x 350Ω load cells or 8 x 700Ω load cells
PERFORMANCE		
Maximum Display Counts		100,000
Analog Signal Input Range – mV/V		4.5
Sensitivity – μV		0.3/graduation min.
Measurement Rate – sec.		30, 15, 7.5, 3.75
ENVIRONMENTAL		
Operating Temperature	°C	-10 to 40
	°F	+14 to +104
POWER		
Power – VDC		9 provided by 6 “C” cells or included AC adaptor
MECHANICAL		
Weight		4.6 lb with batteries
Enclosure		NEMA 4X/IP66 stainless steel
Enclosure Dimensions - W x H x D	mm	228.6 x 140.21 x 76.2
	in	9.0 x 5.52 x 3
Display	mm	6 digit LCD, 25.4
	in	6 digit LCD, 1

OPTIONS

- Carrying case for portable use
- Please specify if CE mark is required



STANDARD CONFIGURATION



MODEL 9390-0 (Shown)